AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

LISTING OF THE CLAIMS:

1. (Currently Amended) A portable device comprising:

a display;

a light detector for detecting the light incident on at least part of the display;

a comparator for comparing the light detected with a given threshold; and and a controller controlling an illuminator for illuminating the display in dependence upon the output of the comparator; and wherein

the light detector is positioned to receive a light level that represents the total light contributing to display illumination which is the sum of the light received from the illuminator and the light incident on the display.

- 2. (Previously Presented) A portable device according to claim 1 wherein the light detector is located behind the display, remote from the surface of the display onto which the ambient light is incident.
- (Previously Presented) A device claimed in claim 1 wherein the controller disables the illuminator in response to an indication by the comparator that the light detected exceeds a first threshold.

- 4. (Previously Presented) A device as claimed in claim 2 wherein the controller enables the illuminator in response to an indication by the comparator that the light detected is less than a second threshold.
- 5. (Previously Presented) A device as claimed in claim 3 wherein the controller enables the illuminator in response to an indication by the comparator that the light detected is less than a second threshold.
- 6. (Previously Presented) A device as claimed in claim 5, wherein the controller partially enables the illuminator in response to an indication by the comparator that the light detected is between the first and second thresholds.
- 7. (Previously Presented) A device as claimed in claim 1, further comprising means for determining a change in output of the light detector over a predetermined period, wherein the control means is arranged to disable functionality relating to the display in response to an indication that no change is determined.
- 8. (Previously Presented) A device as claimed in claim 7, wherein the controller is arranged to disable the display in response to an indication that no change is determined.

- 9. (Previously Presented) A device as claimed in claim 7, wherein the controller is arranged to disable the illuminator in response to an indication that no change is determined.
- 10. (Previously Presented) A device as claimed in claim 1, wherein the display comprises input means responsive to a user.
- 11. (Previously Presented) A device as claimed in claim 10, wherein the controller controls the functionality relating to the display on the basis of settings input by the user via the input means.
- 12. (Currently Amended) A device as claimed n-in claim 10, wherein the input means comprises touch means, such as a key and/or display region.
- 13. (Currently Amended) A device as claimed in claim 1, which is a protable portable communications device such as a radiotelephone.
- 14. (Currently Amended) A method of controlling <u>a</u> handportable device including a display and an illuminator for illuminating the display, the method comprising:

detecting a light level that represents the total light contributing to display illumination which is the sum of the light received from the illuminator and the ambient light incident on at least part of the display;

comparing the light detected with a given threshold; and controlling illumination of the display in dependence upon the output of the comparator.

15. (Currently Amended) A display module for an electronic device, the display module comprising:

a display panel having a front face to be viewed by a user and a reverse face;

a-an illuminator for illumining illuminating the display panel;

a light detector being positioned adjacent the reverse face of the display panel to detect light, which light is the sum of ambient light incident on at least part of the display and the light from the illuminator;

a comparator for comparing the light detected with a given threshold, and a controller controlling the illuminator in dependence on the output of the comparator.

16. (Currently Amended) A display comparing:

a display element;

a light detector for detecting the light incident on at least part of the surface of a display element;

a comparator for comparing the light detected with a given threshold; and a controller controlling an illuminator for illuminating the display in dependence upon the output of the comparator; and wherein

wherein the light detector is positioned to receive a light level that represents the total light contributing to illumination of the display which is the sum of the light received from the illuminator and the ambient light incident on the display.

Claims 17-19, cancelled.

20. (Currently Amended) A display module for an electronic device, the display module comprising:

a display panel having a front face to be viewed by a user and a reverse face;

an illuminator for illuminating the display panel;

a light detector for detecting light incident on at least part of the display panel, the light detector being positioned adjacent the reverse face of the display panel to detect light incident on the device, which light is the sum of ambient light and the light from the illuminator;

a comparator for comparing the light detected by the light detector with a given threshold, and

control means for controlling the illuminator in dependence on the output of the comparator.

Claim 21, cancelled.

22. (New) A device as claimed in claim 12 wherein:

the touch means comprises a key.

23. (New) A device as claimed in claim 12 wherein: the touch means comprises a display region.

24. (New) A device as claimed in claim 12 wherein: the touch means comprises a key and a display region.